

# Medallion

## M-1110 Emboss Only



### M-1110

#### MARKETS

**HOSPITAL  
HEALTH CARE  
NURSING HOMES  
CLINICS**

If you are looking for a low volume, low cost card personalization system the NBS Medallion Series™ embosser is the answer.

Ideal for the instant issuance environment, the Medallion Series allows flexibility for operators to issue cards anywhere, on line or off-line providing enhanced customer service and improved productivity. Just think, your patients will no longer have to wait for cards to be mailed, or sent to another location for pickup. The convenience of instant card issuance will make your organization a customer's first choice.

The Medallion Series, with its small size, quiet operation and flexibility, is the card personalization tool for you.

#### Medallion 1150

When encoding, tipping, indenting or smart card initialization is required, the Medallion 1150 is ideal for those applications. Visit us at [www.nbstech.com](http://www.nbstech.com) for more information on the Medallion 1150 and the entire family of NBS products.

Medallion M-1110

## FEATURES/BENEFITS

The Medallion is designed to interface to your existing computer system using a variety of protocols. The M1110 embosser allows you to make cards off-line (locally with a keyboard) without interrupting on-line use.

A Windows® multi-driver is available to download on our website @ [www.nbstech.com](http://www.nbstech.com)

## PRODUCT SPECIFICATIONS

### STANDARD FEATURES

Keyboard for manual data entry  
120 Character Embossing Wheel  
Fully functional control panel  
Automatic Card Remake  
On-line system software  
Modular design  
RS 232 Serial Communication Interface  
On-line data analyzer  
LCD display (2-lines, 40 characters)  
Field Upgradeable  
95/98, NT Windows® drivers

### SPECIFICATIONS

Embossing Characteristics:

	<u>CR80</u>	<u>CR50</u>
Maximum Lines	10	8
Maximum Simplex characters per line	31	32
Maximum OCR characters per line	22	23
Maximum Blocco characters per line	22	23

Environmental Specifications:

Operating Temp: 58 F-80 F (14 C-27 C)  
Relative Humidity: 20%-85%, Non-condensing

Physical Dimensions:

Width: 18.05inches (73cm)  
Depth: 18.75 inches (48cm)  
Height: 16.50 inches(42cm)  
Weight: Up to 60lbs.

Power Requirements:

110V, 50/60 Hz. 4 Amp

220V, 50/60 Hz, 3 Amp

Speed: 50 Characters per card - 40 seconds

Duty cycle: 100 cards per day

Specifications subject to change without notification

**Advantage Series Embossers meet all applicable FCC, CE, and UL specifications**

---

Card Technology Corporation  
70 Eisenhower Drive  
Paramus NJ 07652 1-800-443-4396  
phone 201-845-7373 fax 201-843-0979  
[www.nbstech.com](http://www.nbstech.com)  
[custservctc@nbstech.com](mailto:custservctc@nbstech.com)

